

STP-3P



Features


1. The housing is available in a variety of colors.
2. Press the pressing plate to enable the contact output function.
3. Resettable design, with a large number of obvious indicators around.
4. Pressing plate is with status shown.
5. With special reset tool, compact appearance, easy to carry and collection.
6. Built-in buzzer status could be set as silent and continuous wailing.
7. Warning light status could be set as continuous flashing and keeping light.
8. Input power range is DC 12-24V, matching the various types of fire alarm system's request.
9. Surface mount without screws and with protect cover, DPDT output.

Specification

Item	Mode	811/812	Remark
Power		DC12-24V	±10%
Working current		DC 12V/ ≤30mA(Standby)/ ≤100mA(trigger)	±10%
		DC 24/ ≤30mA(Standby)/ ≤100mA(trigger)	
Buzzer		Set to silent or buzzer continuously	
Indicator light		Default Green, Active Red; Light can be set as continuous flashing or keep lighting	
Output		2NO/2NC/2COM, DC12V/0.5A	
Weight		200g	
Size		91mm*96mm*34.5mm (with cover)	
Material		ABS,PC. (Cover parts)	


● Standby

Display status: green



● Action


Display status: red



RELATED PRODUCTS



STP-DU04-CP22



STP-EM01-FIRE



STP-KGG200SG



STP-NT200-S